

207433 NAT/PH

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
27 January 2005 (27.01.2005)

PCT

(10) International Publication Number
WO 2005/007559 A2

(51) International Patent Classification⁷: **B67D 1/04**

NL-2628 BA Delft (NL). INNIKEL, Quintijn [NL/NL];
Beresteinseweg 76, NL-1217 TK Hilversum (NL).

(21) International Application Number:

PCT/NL2004/000512

(74) Agent: VAN WESTENBRUGGE, Andries; Nederland-
sch Octrooibureau, Scheveningsweg 82, P.O. Box 29720,
NL-2502 LS The Hague (NL).

(22) International Filing Date: 15 July 2004 (15.07.2004)

(25) Filing Language: Dutch

(26) Publication Language: English

(30) Priority Data:
1023967 21 July 2003 (21.07.2003) NL

(71) Applicant (for all designated States except US):
HEINEKEN TECHNICAL SERVICES B.V. [NL/NL];
Burgemeester Smeetsweg 1, NL-2382 PH Zoeterwoude
(NL).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.


(72) Inventors; and

(75) Inventors/Applicants (for US only): **PAKKERT, En-
gbert, Hermannes** [NL/NL]; Michiel de Ruiterweg 39,

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

[Continued on next page]

(54) Title: DRINK DISPENSER WITH DISPENSING LINE THAT CAN BE HINGED OPEN



(57) Abstract: The invention relates to a drink dispenser provided with a chamber with an opening for accommodating a container containing carbonated drink. The container is provided with an outlet closed by a shut-off valve and a tap head that during use is connected via a line to the outlet, which tap head has an operating member for opening and closing the line, wherein the line has a relatively stiff line section with a first part and a second part that are in contact with one another in a contact plane extending in a longitudinal direction of the line and which can be taken apart to provide access to an interior surface of the line section, wherein sealing means extending in the longitudinal direction of the line section are arranged in or close to the contact plane to form a liquid barrier, and wherein the two line parts have a clamping member that is able to engage on a locking element for fixing the line parts in a position in contact with one another.

WO 2005/007559 A2



ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

- *without international search report and to be republished upon receipt of that report*